



## HOSE TYPE: ¾" VAMAC DN20

- **TUBE:** VAMAC
- **VAMAC COMPOUND:** 7100 TO RSE/STD/004 PART 10
- **REINFORCEMENT:** ONE TEXTILE BRAID (POLYESTER)
- **OVER:** VAMAC
- **HOSE ID:** 19mm (+/- 0.5)
- **HOSE OD:** 29.5mm (+/- 0.5)
- **WORKING PRESSURE:** 20 BAR
- **MINIMUM BURST PRESSURE:** 80 BAR
- **TEMPERATURE RANGE:** -38°C TO +150°C  
*(CONTINUING OPERATING TEMPERATURES IN EXCESS OF THE SPECIFIED RANGE WILL SHORTEN THE LIFE OF THE HOSE)*
- **MINIMUM BEND RADIUS:** 114mm
- **APPROXIMATE WEIGHT:** 0.68kg/m
- **CONFORMS TO:** Westinghouse Specification 9L67/68
- **MEETS FIRE SAFETY REGS:** BS 6853 CAT 1A
- **COMMENTS:** LOW SMOKE, LOW TOXICITY
- **TYPICAL USE:** UNDERGROUND BRAKE HOSE

**BRANDING TYPICALLY:**